

## J Series Tapered Rod

Description	Part Number	Thread Type	Dimensions				Rod Weight	
			Rod Length FT	Rod OD IN	Coupling ID IN	Midbody ID IN	lb.	kg.
			AWJ Ultra light x 1 ft	51 609	5	1ft	1.75	0.625
AWJ Ultra light x 2 ft	51 610	5	2 ft	1.75	0.625	1.470	6.6	3.0
AWJ Ultra light x 5 ft	51 611	5	5 ft	1.75	0.625	1.470	12.5	5.7
AWJ Ultra light x 10 ft	51 612	5	10 ft	1.75	0.625	1.470	24.0	10.9
AWJ HD x 2 ft	51 629.1	5	2ft	1.75	0.625	1.248	9.9	4.5
AWJ HD x 5 ft	51 628	5	5 ft	1.75	0.625	1.248	21.1	9.6
AWJ HD x 10 ft.	51 629	5	10 ft	1.75	0.625	1.248	40.9	18.6
AWJ x 1 ft	51 600.1	5	1ft	1.75	0.625	1.374	5.0	2.3
AWJ x 2 ft	51 600.2	5	2 ft	1.75	0.625	1.374	8.8	4.0
AWJ x 5 ft	51 601	5	5 ft	1.75	0.625	1.374	16.5	7.5
AWJ x 10 ft.	51 602	5	10 ft	1.75	0.625	1.374	32.0	14.5
BWJ x 1 ft	51 614.10	5	1ft	2.1	0.823	1.75	7.0	3.2
BWJ x 2 ft	51 614.2	5	2 ft	2.1	0.823	1.75	11.0	5.0
BWJ x 5 ft	51 626	5	5 ft	2.1	0.823	1.75	21.0	9.5
BWJ x 10 ft	51 627	5	10 ft	2.1	0.823	1.75	40.0	18.2
NWJ x 1 ft	51 650.1	5	1ft	2.625	1.126	2.250	9.0	4.1
NWJ x 2 ft	51 650.2	5	2 ft	2.625	1.126	2.250	14.3	6.5
NWJ x 5 ft	51 651	5	5 ft	2.625	1.126	2.250	27.0	12.3
NWJ x 10 FT	51 652	5	10 ft	2.625	1.126	2.250	51.0	23.2

### Material:

**AW HD rod is made with a coupling and heavier wall midbody. All other sizes are made in one piece with a friction welded end. Couplings are heat treated to provide added toughness.**

**We can also supply BW and NW rod with couplings - please contact us with your requirement**