

# Core drilling tools

## Wireline drill rods

IMPERIAL LENGTH DRILL ROD



Sandvik has brought together some of the industry's most outstanding know-how, products, techniques and equipment to provide a unique offering in the area of exploration drilling.

Sandvik's comprehensive global organization ensures that our customers have a reliable partner.

## WIRELINE DRILL ROD - IMPERIAL LENGTHS



Sandvik's quench and temper heat treatment of box and pin ends increases threaded joint strength for greater depth capacity and longer life.

- High quality alloy steel is manufactured to Sandvik specifications and supplied by qualified vendors.
- All materials are tested and benchmarked in Sandvik Material Technology's state of the art materials laboratory.
- Machining expertise provided by a team of seasoned professionals.



Box end of finished rods are coated with a unique, environmentally friendly, anti-galling thread compound.

- Outside diameter and pin end of rod is coated in environmentally friendly rust inhibitor.

Part No	Description	Length	ID	OD	Weight
<b>Industry Standard Thread</b>					
BB00000044	Drill Rod, B	5 ft	1.815 in	2.189 in	21 lb
BB00000045	Drill Rod, B	10 ft	1.815 in	2.189 in	42 lb
BB00000046	Drill Rod, N	5 ft	2.374 in	2.752 in	27 lb
BB00000047	Drill Rod, N	10 ft	2.374 in	2.752 in	53 lb
BB00000048	Drill Rod, H	5 ft	3.063 in	3.500 in	40 lb
BB00000050	Drill Rod, H	10 ft	3.063 in	3.500 in	79 lb
<b>"T" Thread</b>					
BB00000057	Drill Rod, BT	5 ft	1.815 in	2.189 in	21 lb
BB00000058	Drill Rod, BT	10 ft	1.815 in	2.189 in	42 lb
BB00000059	Drill Rod, NT	5 ft	2.374 in	2.752 in	27 lb
BB00000060	Drill Rod, NT	10 ft	2.374 in	2.752 in	53 lb
BB00000061	Drill Rod, HT	5 ft	3.063 in	3.500 in	40 lb
BB00000062	Drill Rod, HT	10 ft	3.063 in	3.500 in	79 lb

**NOTE:** For 2 ft rod lengths use 0.6 m rod lengths. Please contact your Sandvik representative.

P (HWT) and S (PWT) size drill rod is available in metric lengths only. Please contact your Sandvik representative.

Bundle Detail	# of Rods	Length	Width	Height	Weight
Drill Rod, B/BT	19	5.23 ft	11.4 in	10.0 in	406 lb
Drill Rod, B/BT	19	10.23 ft	11.4 in	10.0 in	795 lb
Drill Rod, N/NT	19	5.23 ft	14.0 in	12.6 in	513 lb
Drill Rod, N/NT	19	10.23 ft	14.0 in	12.6 in	1007 lb
Drill Rod, H/HT	19	5.23 ft	18.5 in	16.0 in	768 lb
Drill Rod, H/HT	19	10.23 ft	18.5 in	16.0 in	1509 lb



Finished rods are bundled and transferred to Sandvik Logistics, a focused business unit within the Group responsible for the inventory and distribution of products around the globe.