



Percussion and Rotary Drill Rod

Up to 4.5 in Outside Diameter - USA (Ft.) Lengths

Thread Type	Part Number	Description	Length		Rod O. D.		I.D. at End		Wall Thick.		Weight	
			ft.	mm.	inch	mm.	inch	mm.	inch	mm.	lb.	kg.
RD 50-6	52 051 015	PR 70	1.5	457.2	2.75	69.9	0.98	25	0.189	4.80	26.4	12
RD 50-6	52 052 050	PR 70	5.0	1524.0	2.75	69.9	0.98	25	0.189	4.80	35.2	16
RD 50-6	52 054 100	PR 70	10.0	3048.0	2.75	69.9	0.98	25	0.189	4.80	59.4	27
2 3/8 API REG	52 101 015	PR 76	1.5	457.2	2.99	76.0	1.18	30	0.157	4.00	24.2	11
2 3/8 API REG	52 102 050	PR 76	5.0	1524.0	2.99	76.0	1.18	30	0.157	4.00	33.0	15
2 3/8 API REG	52 104 100	PR 76	10.0	3048.0	2.99	76.0	1.18	30	0.157	4.00	55.0	25
2 3/8 API REG	52 126 015	PR 76 Heavy Duty	1.5	457.2	2.99	76.0	1.18	30	0.249	6.35	33.0	15
2 3/8 API REG	52 127 050	PR 76 Heavy Duty	5.0	1524.0	2.99	76.0	1.18	30	0.249	6.35	44.0	20
2 3/8 API REG	52 129 100	PR 76 Heavy Duty	10.0	3048.0	2.99	76.0	1.18	30	0.249	6.35	79.2	36
2 3/8 API REG	52 401 015	PR 89	1.5	457.2	3.50	89.1	1.18	30	0.157	4.00	35.2	16
2 3/8 API REG	52 402 050	PR 89	5.0	1524.0	3.50	89.1	1.18	30	0.157	4.00	41.8	19
2 3/8 API REG	52 404 100	PR 89	10.0	3048.0	3.50	89.1	1.18	30	0.157	4.00	68.2	31
2 3/8 API REG	52 476 015	PR 89 Heavy Duty	1.5	457.2	3.50	89.1	1.18	30	0.249	6.35	39.6	18
2 3/8 API REG	52 477 050	PR 89 Heavy Duty	5.0	1524.0	3.50	89.1	1.18	30	0.249	6.35	55.0	25
3 1/2 API REG	52 479 100	PR 89 Heavy Duty	10.0	3048.0	3.50	89.1	1.18	30	0.249	6.35	96.8	44
3 1/2 API REG	52 702 050	PR 114	5.0	1524.0	4.49	114.3	1.65	42	0.249	6.35	79.2	36
3 1/2 API REG	52 704 100	PR 114	10.0	3048.0	4.49	114.3	1.65	42	0.249	6.35	134.2	61
3 1/2 API REG	52 705 150	PR 114	15.0	4572.0	4.49	114.3	1.65	42	0.249	6.35	191.4	87
3 1/2 API REG	52 706 200	PR 114	20.0	6096.0	4.49	114.3	1.65	42	0.249	6.35	24.2	11
4 1/2 API REG	32 1018 050	PR 140	5.0	1524.0	5.49	139.7	2.24	57	0.249	6.35	114.4	52
4 1/2 API REG	32 1020 100	PR 140	10.0	3048.0	5.49	139.7	2.24	57	0.249	6.35	182.6	83
4 1/2 API REG	32 1021 150	PR 140	15.0	4572.0	5.49	139.7	2.24	57	0.249	6.35	257.4	117
4 1/2 API REG	32 1022 200	PR 140	20.0	6096.0	5.49	139.7	2.24	57	0.249	6.35	321.2	146