



J Tapered Rod

Description	Part Number	Threads Per inch	Length		Rod O. D.		I.D. at End		Weight	
			ft.	mm.	inch	mm.	inch	mm.	lb.	kg.
AWJ	21156-1	5	1.0	304.8	1.750	44.4	0.625	15.9	5.0	2.3
AWJ	21156-9	5	2.0	609.6	1.750	44.4	0.625	15.9	8.8	4.0
AWJ	BSJ21156-6	5	5.0	1524.0	1.750	44.4	0.625	15.9	16.5	7.5
AWJ	21156-7	5	10.0	3048.0	1.750	44.4	0.625	15.9	32.0	14.5
BWJ	21158-1	5	1.0	304.8	2.100	53.3	0.823	20.9	7.0	3.2
BWJ	21158-9	5	2.0	609.6	2.100	53.3	0.823	20.9	11.0	5.0
BWJ	21158-6	5	5.0	1524.0	2.100	53.3	0.823	20.9	21.0	9.5
BWJ	21158-7	5	10.0	3048.0	2.100	53.3	0.823	20.9	40.0	18.2
NWJ	21157-1	5	1.0	304.8	2.625	66.7	1.126	28.6	9.0	4.1
NWJ	21157-9	5	2.0	609.6	2.625	66.7	1.126	28.6	14.3	6.5
NWJ	21157-6	5	5.0	1524.0	2.625	66.7	1.126	28.6	27.0	12.3
NWJ	21157-6	5	10.0	3048.0	2.625	66.7	1.126	28.6	51.0	23.2

J rod is made of a high strength threaded end or tool joint welded to a mid body.



W Series Coupled Rod

Description	Part Number	Threads Per inch	Length		Rod O. D.		Rod ID		Weight	
			ft.	mm.	inch	mm.	inch	mm.	lb.	kg.
AW	021005-1	5	1.0	304.8	1.750	44.4	1.250	31.8	4.3	2.0
AW	021005-2	5	2.0	609.6	1.750	44.4	1.250	31.8	8.6	3.9
AW	021005-5	5	5.0	1524.0	1.750	44.4	1.250	31.8	21.5	9.8
AW	021005-10	5	10.0	3048.0	1.750	44.4	1.250	31.8	43.0	19.5
AW Coupling	110005	5	NA	NA	1.750	44.4	0.625	15.8	2.0	0.9
BW	021006-1	5	1.0	304.8	2.125	54.0	1.750	44.5	7.0	3.2
BW	021006-1	5	2.0	609.6	2.125	54.0	1.750	44.5	14.0	5.0
BW	021006-25	5	5.0	1524.0	2.125	54.0	1.750	44.5	33.0	15.0
BW	021006-26	5	10.0	3048.0	2.125	54.0	1.750	44.5	60.0	27.3
BW Coupling	110006	5	NA	NA	2.125	54.0	0.750	19.1	3.5	1.6
NW	021007-1	5	1.0	304.8	2.625	66.7	2.125	54.0	9.0	4.1
NW	021007-1	5	2.0	609.6	2.625	66.7	2.125	54.0	14.3	6.5
NW	021007-32	5	5.0	1524.0	2.625	66.7	2.125	54.0	45.0	20.5
NW	021007-31	5	10.0	3048.0	2.625	66.7	2.125	54.0	85.0	38.6
NW coupling	110007	5	NA	NA	2.635	66.9	1.375	34.9	5.5	2.5
Material		W series rod is made of a high strength threaded mid body with a heat treated coupling								