



Heat Treated Wireline Drill Rod

In Metric and Foot Lengths

Description	Part Number	Thread Type	Dimensions				Rod Weight		
			Rod Length	OD	OD	ID	ID	lb.	kg.
				MM	IN	MM	IN		
B-WL x 1500 mm	BR3605	3	1.5 M	55.60	2.19	46.000	1.811	20.1	9.1
B-WL x 3000 MM	BR3610	3	3.0 M	55.60	2.19	46.000	1.811	40.2	18.3
B-WL X 2 Ft	BR3102	3	2 ft	66.60	2.19	46.000	1.811	10.0	4.5
B-WL x 5 FT	BR3105	3	5 ft	55.60	2.19	46.000	1.811	20.1	9.1
B-WL x 10ft	BR3110	3	10 ft	55.60	2.19	46.000	1.811	40.2	18.3
N-WL x 1500 mm	N3605	3	1.5 M	69.90	2.75	60.300	2.374	26.2	11.9
N-WL x 3000 MM	N3610	3	3.0 M	69.90	2.75	60.300	2.374	52.4	23.8
N-WL X 2 FT	N3102	3	2 ft	69.90	2.75	60.300	2.374	13.0	5.9
N-WL x 5 FT	N3105	3	5 ft	69.90	2.75	60.300	2.374	26.2	11.9
N-WL x 10ft	N3110	3	10 ft	69.90	2.75	60.300	2.374	52.4	23.8
H-WL x 1500 mm	H3605	3	1.5 M	88.9	3.5	77.800	3.06	38.5	17.5
H-WL x 3000 MM	H3610	3	3.0 M	88.9	3.5	77.800	3.06	77.0	35.0
H-WL X 2 FT	H3602	3	2 ft	88.9	3.5	77.800	3.06	19.0	8.6
H-WL x 5 FT	H3605	3	5 ft	88.9	3.5	77.800	3.06	38.5	17.5
H-WL x 10ft	H3610	3	10 ft	88.9	3.5	77.800	3.06	77.0	35.0
HWT x 1500 mm	HWT3605	3	1.5 M	117.800	4.638	103.400	4.071	53.5	24.3
HWT x 3000 MM	HWT3610	3	3.0 M	117.800	4.638	103.400	4.071	102.6	46.6
HWT x 2 FT	HWT3102	3	2 ft	117.800	4.638	103.400	4.071	26.5	12.0
HWT x 5 FT	HWT3105	3	5 ft	117.800	4.638	103.400	4.071	53.5	24.3
HWT x 10ft	HWT3110	3	10 ft	117.800	4.638	103.400	4.071	102.6	46.6

Material:

Made from high yield strength cold drawn 4130 steel with Heat treated ends

Available in additional lengths. Please also contact us for Heavy Duty wireline Rod withn welded tool joint ends



Heat Treated Thin Kerf Wireline Drill Rod

In Metric and Foot Lengths

Description	Part Number	Thread Type	Dimensions					Rod Weight	
			Rod Length	OD		ID		lb.	kg.
				MM	IN	MM	IN		
BTW x 1500 mm	BTW6605	3	1.5 M	56.515	2.225	48.489	1.909	17.0	7.7
BTW x 3000 MM	BTW6610	3	3.0 M	56.515	2.225	48.489	1.909	34.0	15.5
BTW X 2 Ft	BTW6102	3	2 ft	56.515	2.225	48.489	1.909	7.5	3.4
BTW x 5 FT	BTW6105	3	5 ft	56.515	2.225	48.489	1.909	17.5	8.0
BTW x 10ft	BTW6110	3	10 ft	56.515	2.225	48.489	1.909	34.5	15.7
NTW x 1500 mm	NTW6605	3	1.5 M	73.025	2.875	64.135	2.525	24.5	11.1
NTW x 3000 MM	NTW6610	3	3.0 M	73.025	2.875	64.135	2.525	49.5	22.5
NTW X 2 FT	NTW6102	3	2 ft	73.025	2.875	64.135	2.525	10.0	4.5
NTW x 5 FT	NTW6105	3	5 ft	73.025	2.875	64.135	2.525	15.0	6.8
NTW x 10ft	NTW6110	3	10 ft	73.025	2.875	64.135	2.525	50.0	22.7
HTW x 1500 mm	HTW6605	3	1.5 M	88.9	3.500	*	*	38.5	17.5
HTWx 3000 MM	HTW6610	3	3.0 M	88.9	3.500	*	*	77.0	35.0
HTW X 2 FT	HTW6102	3	2 ft	88.9	3.500	*	*	13.6	6.2
HTWx 5 FT	HTW6105	3	5 ft	88.9	3.500	*	*	34.0	15.5
HTW x 10ft	HTW6110	3	10 ft	88.9	3.500	*	*	68.0	30.9

Material:

Made from high yield strength cold drawn 4130 steel with Heat treated ends
 Available in additional lengths. Please also contact us for Heavy Duty wireline Rod with